

pewag SSWI Safety shackle


Withstands any vibrations.

Yet another quality product made from high-grade steel that is forged, stamped and tested to within an inch of its life before it is put to use. This stainless steel safety shackle with a reinforced suspension bolt is designed for use as an end fitting in chain and wire rope slings and in connection with pump chains for the lifting of submersible pumps and breathers, where maximum safety is key. The product comes with a safety mechanism to protect against unintentional release. Please note that it cannot be mounted directly onto the chain.

If used correctly, the SSWI Safety shackle easily withstands vibrations. Each of these safety products bears the CE mark and has a code on the bolt and pins for added traceability.

Preferred areas of application for the shackle are water and wastewater applications and the product can also be used in connection with chemicals and food products; however, restrictions will apply and we recommend that you contact the manufacturer for advice prior to exposing the product to such use.



SSWI Safety shackle	Code	WLL [kg]	e [mm]	a [mm]	b [mm]	d [mm]	d1 [mm]	c [mm]	Weight [kg/pc.]
	SSWI 0,5 t-S	500	33	8	18	8	9	18	0.07
	SSWI 1,25 t-S	1,250	40	12	25	12	13	25	0.22
	SSWI 2 t-S	2,000	60	16	32	16	17	32	0.52
	SSWI 3,2 t-S	3,200	78	19	41	19	21	47	0.80
	SSWI 5 t-S	5,000	109	25	56	25	29	60	2.2
	SSWI 26-C	13,000	152	34	76	34	38	75	7

Other sizes and special models available on request! On request also stronger shackles available.

Bolt safety mechanism:

S = with safety splint

C = with bolt adhesive

